


Customer Information Sheet

DRAWING No.: M80-FB1XX05FC-XXXXFC IF IN DOUBT - ASK © NOT TO SCALE THIRD ANGLE PROJECTION ALL DIMENSIONS IN mm



- NOTES:
- 1. CABLE ASSEMBLIES WILL BE BULK PACKED IN BAGS.
 - 2. FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C005XX (LATEST ISSUE) AND C049XX (LATEST ISSUE).
 - 3. WIRING OF CONNECTOR:
CONTACT 1 TO CONTACT 1,
CONTACT 2 TO CONTACT 2, ETC.

DIMENSION	MEASUREMENT
DIM 'A'	TOTAL No. OF CONTACTS - 2.00
DIM 'B'	TOTAL No. OF CONTACTS + 5.00
DIM 'C'	TOTAL No. OF CONTACTS + 10.0
EXAMPLE PART No.:	
2 x 10 CONTACT CONNECTOR WITH 150mm OF 22AWG WIRE = M80-FB11005FC-0150FC	
2 x 50 CONTACT CONNECTOR WITH 450mm OF 22AWG WIRE = M80-FB15005FC-0450FC	

ORDER CODE:
M80-FB1XX05FC-XXXXFC

TOTAL No. OF CONTACTS:
04 TO 50
EVEN NUMBERS ONLY

DIM 'D' LENGTH:
0060 = 60mm MIN
9999 = 9999mm MAX
(SEE TABLE FOR EXAMPLES)

RTP	6	10.03.21	30103
NAME	ISS.	DATE	CN/CO
APPROVED: R.PORTLOCK			
CHECKED: R.ALEXANDER			
DRAWN: R.PORTLOCK			
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN
www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.50mm
X.XX = ±0.20mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL:
SEE ABOVE
FINISH: SEE ABOVE
S/AREA: mm²

TITLE: M80 FEMALE-TO-FEMALE
T-CONTACT CABLE
ASSY WITH 10ILOK JACKSCREWS
DRAWING NUMBER:
M80-FB1XX05FC-XXXXFC
SHT 2 OF 2